



**CHRISTIES**  
**REPAIRS**  
AND MAINTENANCE

EK - RANGE




EK

- Resistenze elettriche corazzate AISI 321 avvolte a profilo ad alto scambio termico
  - Termostato ambiente incorporato
  - Selettore di potenza
  - Cavo alimentazione elettrica (1,5 m) con spina (EK 3)
  - Termostato di sicurezza a riarmo manuale
  - Griglia anteriore in acciaio inox
  - Canalizzabile fino a 6 m (EK 10, EK 15)
  - Possibilità di impilamento
- Extra strength elements AISI 321 for high performance
  - Built-in room thermostat
  - Selector switch
  - Power cord (1,5 m) with plug (EK 3)
  - Safety thermostat with manual reset
  - Stainless steel front grid
  - Ductable up to 6 m long (EK 10, EK 15)
  - Possibility to stackability




### ACCESSORI A RICHIESTA / ACCESSORIES ON DEMAND

SPINA 4-5 POLI 4-5 PIN PLUG	ADATTATORE GUAINA DUCT ADAPTER	GUAINA FLESSIBILE IN PVC L= 6 m CON CINGHIA DI FISSAGGIO Ø 300 mm FLEXIBLE AIR DUCT 6 m LONG WITH CLIP Ø 300 mm	KIT CARRELLO TROLLEY KIT
			
Mod. 3P+ - EK 10 Cod. 05AC102 15A	Mod. EK 10 - EK 15 Cod. 05AC101	Mod. EK 10 - EK 15 Cod. 02AC562	Mod. EK 10 - EK 15 Cod. 03AC501
Mod. 3P+ - EK 15 Cod. 05AC103 32A			
Mod. 3P+ - 4N EK 10 Cod. 05AC104 15A			
Mod. 3P+ - 4N EK 15 Cod. 05AC105 32A			



PESI E DIMENSIONI MACCHINA WEIGHTS AND DIMENSIONS MACHINE					IMBALLO PACKAGING			
MOD	A	B	C	Netto/Net	X	Y	H	Lordo/Gross
	[mm]	[mm]	[mm]	[kg]	[mm]	[mm]	[mm]	[kg]
EK 3 C	367	180	280	5	382	277	217	6
EK 10 C	506	277	511	15	542	387	315	14
EK 15 C	575	277	511	15	610	387	315	16

		EK 3 C	EK 10 C	EK 15 C
codice - code		05EK101	05EK102	05EK103
potenza term. nominale max max rated heat power	Hs [kW] Hs [heat/h - BTU/h]	3 2.580 - 10.235	10 8.600 - 34.120	15 12.900 - 51.185
potenza term. nominale min. min rated heat power	Hs [kW] Hs [heat/h - BTU/h]	1,5 1.290 - 5.185	6,5 5.675 - 22.520	10 8.600 - 34.120
rendimento - heat efficiency	[%]	100	100	100
portata d'aria - air flow	[m <sup>3</sup> /h]	450	1.500	2.000
salto termico - temperature rise	a 20°C [°C]	44,5 - 32	48,3 - 30,5	54,3 - 35
corrente massima - current max	[A]	13 - 6,5	13,6 - 7,1	21 - 13,8
alimentazione elettrica - electric power	[V - ph - Hz]	230 - 1 - 50	400 - 3 - 50	400 - 3 - 50
quantità per pallet - pallet quantity	[pz - pcs]	72	36	24



**CHRISTIES**  
**REPAIRS**  
AND MAINTENANCE

13 ASBESTOS ROAD, DAGGAFONTEIN, SPRINGS

[WWW.CHRISTIES.CO.ZA](http://WWW.CHRISTIES.CO.ZA)

011-363-0722 / 2458 / 6005

[jacques@christies.co.za](mailto:jacques@christies.co.za)

[deon@christies.co.za](mailto:deon@christies.co.za)

[m.christie@christies.co.za](mailto:m.christie@christies.co.za)

VAT: 4240202863 – REG: 2002 / 096148 / 23

BEE – Level 4